



# Safety Data Sheet

## REMA Tire Repair Materials

Product #: RTT- 40

SDS #: RTT-TRM-228

Rev. # 1

Rev. Date: 2/17/2023

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** RTT-40 Rema RE-LEASE

**Chemical Family:** Aliphatic Hydrocarbons

**Product Use:** Aerosol Penetrant

**Restrictions on Use:** Use as directed by manufacturer

**Distributed by:** Rema Tip Top/North America, Inc  
1500 Industrial Blvd.  
Madison, GA 30650  
Phone: 706-752-4000

**24-Hour Emergency Phone Number:** North America: 800-424-9300 (CHEMTREC)  
International: 703-527-3887 (CHEMTREC) Collect Calls Accepted

### 2. HAZARDS IDENTIFICATION

#### GHS Classification

##### Health Hazards

Skin Irritation, Category 2

Eye Irritation, Category 2A

Aspiration Hazard, Category 1

Specific Target Organ Systemic Toxicity, Single Exposure, Category 3, Central Nervous System [Inhalation, Ingestion]

##### Physical Hazards

Flammable Aerosol, Category 1

Gases under pressure - Liquefied Gas

#### GHS Labeling

##### Pictograms:





# Safety Data Sheet

## REMA Tire Repair Materials

Product #: RTT- 40

SDS #: RTT-TRM-228

Rev. # 1

Rev. Date: 2/17/2023

**Signal Word: Danger!**

### Hazard Statements

H222: Extremely flammable aerosol  
H280: Contains gas under pressure, may explode if heated  
H304: May be fatal if swallowed and enters airways  
H315: Causes skin irritation  
H319: Causes serious eye irritation  
H336: May cause drowsiness or dizziness  
H411: Toxic to aquatic life with long lasting effects

### Precautionary Statements

#### Prevention:

P210: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
P211: Do not spray on an open flame or other ignition source.  
P251: Pressurized container: Do not pierce or burn, even after use.  
P261: Avoid breathing vapors.  
P264: Wash hands and exposed skin thoroughly after handling.  
P271: Use only outdoors or in a well-ventilated area.  
P273: Avoid release to the environment.  
P280: Wear protective gloves/eye protection/face protection.

#### Response:

P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
P302 + P352: IF ON SKIN: Wash with plenty of soap and water.  
P304 + P340 + P312: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing; call a POISON CENTER or doctor/physician if you feel unwell..  
P305 + P351 + P338: IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do-continue rinsing.  
P331: Do NOT induce vomiting.  
P332 + P313: If skin irritation occurs: Get medical advice/attention.  
P337 + P311: If eye irritation persists; call a POISON CENTER or doctor/physician  
P362: Take off contaminated clothing and wash before reuse.  
P391: Collect spillage.

#### Storage:

P403 + P233: Store in a well-ventilated place. Keep container tightly closed.  
P405: Store locked up.  
P410 + P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C (122°F).

#### Disposal:

P501: Dispose of contents/container in accordance with local/regional/national regulations.



# Safety Data Sheet

## REMA Tire Repair Materials

Product #: RTT- 40

SDS #: RTT-TRM-228

Rev. # 1

Rev. Date: 2/17/2023

### 3. COMPOSITION/ INFORMATION ON INGREDIENTS

#### Chemical characterization

| Component*                               | CAS #      | Weight % |
|--|------------|----------|
| Solvent naphtha (petroleum) heavy aliph. | 64742-96-7 | 40 - 60  |
| Aliphatic Petroleum Distillate           | 64742-47-8 | 40 - 60  |
| Carbon Dioxide                           | 124-38-9   | 1 - 20   |

\*The above listed components are OSHA hazardous materials which contribute to this products' GHS Hazard Categorization as prescribed in OSHA's Hazard Communication 29 CFR 1910.1200.

### 4. FIRST AID MEASURES

#### Inhalation

**Symptoms & Effects:** Nausea, headache, dizziness, drowsiness, irritation of the nose, throat and lungs

**Measures:** Immediately move outdoors or to fresh air. If not breathing or if breathing is difficult, provide artificial respiration or oxygen. If irritation occurs, seek medical attention.

#### Skin Contact

**Symptoms & Effects:** Slight skin irritation, redness

**Measures:** Wash contaminated areas with plenty of water after use. Wash contaminated clothing before reuse. If skin irritation persists, seek medical attention.

#### Eye Contact

**Symptoms & Effects:** Slight eye irritation, redness

**Measures:** Immediately flush eyes gently with plenty of water for at least 15 minutes. While washing, remove contact lenses if present and easy to do so and continue rinsing. Rinse beneath eyelids by holding eyelids apart with clean fingers while washing. If eye irritation persists, seek medical attention.

#### Ingestion

**Symptoms & Effects:** Stomach or intestinal irritation, nausea, vomiting, dizziness, drowsiness

**Measures:** Seek immediate medical attention. If awake and alert, rinse mouth and drink plenty of water to help dilute the material. Do NOT induce vomiting as this substance is an aspiration hazard. Do not give liquids to a drowsy or unconscious person. If vomiting occurs, keep heads below hips to prevent aspiration.



# Safety Data Sheet

## REMA Tire Repair Materials

Product #: RTT- 40

SDS #: RTT-TRM-228

Rev. # 1

Rev. Date: 2/17/2023

---

### 5. FIRE FIGHTING MEASURES

**Suitable Extinguishing Media:** Dry chemical, Carbon dioxide, Alcohol-resistant foam, Water spray

**Unsuitable Extinguishing Media:** Direct water jet

**Hazardous Combustion Products:** Carbon monoxide, Carbon dioxide

**Protective Equipment for Fire-Fighters:** Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

**Precautions for Fire-Fighters:** Do not use direct water jets on the burning product as they could cause a steam explosion and spread the fire. Water may be ineffective for extinguishment, unless used under favorable conditions. Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Use water spray to cool fire exposed containers and structures if this can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

### 6. ACCIDENTAL RELEASE MEASURES

**Protective Equipment:** Recommended to wear chemical splash goggles & gloves and discard of gloves that show tears, pinholes, or signs of wear. Wear proper garments to reduce skin exposure, such as long-sleeves and pants.

**Personal Precautions:** Persons not wearing proper PPE should be excluded from the area of contamination until clean-up has been completed. Ensure adequate ventilation. Eliminate all ignition sources and pay attention to the spreading of gases, especially at ground level.

**Environmental Precautions:** Do not allow discharge into drains, surface waters, or sanitary sewer system. Prevent spreading over a wide area by constructing a dike or using oil barriers. Local authorities should be advised if significant spillages cannot be contained or if material discharges into drains or ground water.

**Methods & Materials for Clean-Up:** Immediately evacuate the spilled area and provide maximum ventilation. Only personnel equipped with proper eye, and skin protection should be permitted in the area. Eliminate all ignition sources from the area. All equipment used when handling the product must be grounded. Use clean, non-sparking tools to collect absorbed material. Construct a dike to contain spill. Contain spilled material with inert, non-combustible absorbent materials such as sand, earth, diatomaceous earth, or vermiculite. After all visible traces have been removed, thoroughly wet vacuum the area. Do not allow spilled material to enter public drainage system or open water courses. Transfer to a suitable container for disposal according to proper federal, state, and local regulations. Notify the proper response units and agencies for any uncontained releases or spills.



# Safety Data Sheet

## REMA Tire Repair Materials

Product #: RTT- 40

SDS #: RTT-TRM-228

Rev. # 1

Rev. Date: 2/17/2023

### 7. HANDLING AND STORAGE

**Handling:** Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear proper PPE when handling this product including protective gloves, chemical splash goggles, and impervious clothing. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material.

**Storage:** Store in a cool, well- ventilated area, away from heat and ignition sources as well as from incompatible materials (see below). Keep container tightly closed and store locked up. Keep away from food, drink, and animal foodstuffs.

**Incompatible Materials:** Strong oxidizing agents

### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### **Exposure Limits :**

Exposure Limits have not been established for this product.

#### **Carbon Dioxide CAS # 124-38-9**

|       |                                     |                                      |
|-------|-------------------------------------|--------------------------------------|
| OSHA  | Permissible Exposure Limit (PEL)    | 5,000 ppm (9,000 mg/m <sup>3</sup> ) |
| ACGIH | Time Weighted Average (TWA)/(STEL)s | 5,000 ppm/30,000 ppm                 |
| NIOSH | Recommended Exposure Limit (REL)    | 5,000 ppm (9,000 mg/m <sup>3</sup> ) |

**Engineering Controls:** Use product in a well-ventilated area.

**Occupational Exposure Controls:** Ensure adequate ventilation, especially in confined areas. Consider all potential hazards of this material, applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting PPE. Ensure that eyewash stations and safety showers are proximal to the work location. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

**Protective and Hygiene Measures:** Wash hands before breaks and after handling product. When using, do not eat, drink, or smoke. In case of clothes contamination, remove and wash contaminated clothing before re-use.

**Eye Protection:** Recommended to wear splash goggles when there is potential for the exposure of the eyes to the product. Have a suitable eye wash station or bottle nearby in case of splashing into the eyes.

**Hand Protection:** Recommended to wear gloves when using this product, and to discard of gloves that show tears, pinholes, or signs of wear.



# Safety Data Sheet

## REMA Tire Repair Materials

Product #: RTT- 40

SDS #: RTT-TRM-228

Rev. # 1

Rev. Date: 2/17/2023

**Skin Protection:** Wear long-sleeved clothing, pants and proper foot covering in order to minimize direct skin contact. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

**Respiratory Protection:** A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be needed if overexposure is likely to occur. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release or other circumstances where an air-purifying respirator may not provide adequate protection.

### **9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance:** Pale Yellow Liquid

**Odor:** Hydrocarbon solvent-like

**Odor Threshold:** No data available

**pH:** No data available

**Melting/Freezing Point:** No data available

**Boiling point/range:** 300 - 550°F (150 - 290°C)

**Flash point (Tag closed cup):** 150°F (66°C)

**Evaporation rate:** < 1 Ethyl Ether

**Flammability: Lower Limit:** 1.0% (V) **Upper Limit:** 6.0% (V)

**Vapor pressure:** 88 psig @ 70°F (21°C)

**Relative vapor density:** No data available

**Density:** 0.9 g/cm<sup>3</sup> (7.5 lb/gal) @ 60°F (16°C)

**Solubility in water:** Negligible

**Partition coefficient (n-octanol/water):** No data available

**Auto-ignition temperature:** 449°F (232°C)

**Ignition temperature:** No data available

**Decomposition temperature:** No data available

**Viscosity (dynamic):** 1.5 – 2.0 mm<sup>2</sup>/s @ 104°F (40°C)

### **10. STABILITY AND REACTIVITY**

**Reactivity:** Oxidizes with exposure to air.

**Chemical Stability:** Stable under normal conditions.

**Possibility of Hazardous Reactions:** Oxidizes with exposure to air.

**Conditions to Avoid:** Excessive heat, repeated direct sunlight exposure, repeated air exposure

**Incompatible Materials:** Strong oxidizing agents

**Hazardous decomposition products:** Carbon monoxide, Carbon dioxide



# Safety Data Sheet

## REMA Tire Repair Materials

Product #: RTT- 40

SDS #: RTT-TRM-228

Rev. # 1

Rev. Date: 2/17/2023

### 11. TOXICOLOGICAL INFORMATION

**Primary Routes of Exposure:** Skin contact, Eye contact, Inhalation

**Symptoms Related to Physical, Chemical and Toxicological Characteristics:** Nausea, irritation of the nose, throat and airways, dizziness, drowsiness, and headache. This substance is an aspiration hazard.

**Delayed and Immediate Effects & Chronic Effects from Exposure:** This material may lead to central nervous system depression and effects such as dizziness and drowsiness.

**Measures of Toxicity:**

Acute toxicities are calculated based on component toxicities.  
Mixture: Acute Oral Toxicity: LD<sub>50</sub> Rat: > 5,000 mg/kg  
Acute Dermal Toxicity: LD<sub>50</sub> Rabbit: > 2,000 mg/kg  
Acute Inhalation Toxicity: LC<sub>50</sub> Rat: > 470,000 ppm

**Carcinogen Claims:**

OSHA: **None**, International Agency for Research on Cancer (IARC): **None**  
ACGIH: **None**, National Toxicology Program (NTP) Report on Carcinogens: **None**

### 12. ECOLOGICAL INFORMATION

**Eco-toxicity:** No data available  
**Persistence & Degradability:** No data available  
**Bio-accumulative Potential:** No data available  
**Mobility in Soil:** No data available  
**Other Adverse Effects:** No data available

### 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with Federal, State or Local regulations.  
Contaminated packaging should be emptied as far as possible before disposal.



# Safety Data Sheet

## REMA Tire Repair Materials

Product #: RTT- 40

SDS #: RTT-TRM-228

Rev. # 1

Rev. Date: 2/17/2023

---

### 14. TRANSPORT INFORMATION

#### DOT SHIPPING CLASSIFICATION:

UN NUMBER: UN1950

PROPER SHIPPING NAME: Aerosols, flammable, n.o.s. (Aliphatic Petroleum Distillate)

TRANSPORTATION HAZARD CLASS: 2.1

PACKING GROUP: II

HAZARD LABEL: 2.1

#### IMDG (Marine) SHIPPING CLASSIFICATION:

IMDG CODE: 2.1

UN NUMBER: UN1950

MARINE POLLUTANT: Yes

EmS: F-D; S-U

IMDG PACKING GROUP: II

HAZARD LABEL: 2.1

#### Description of the goods

AEROSOLS, flammable, n.o.s. (Aliphatic Petroleum Distillate)

#### IATA (Air) SHIPPING CLASSIFICATION:

ICAO/IATA-DGR: 2.1

UN NUMBER: UN1950

HAZARD LABEL: 2.1

#### Description of the goods

Aerosols, flammable, n.o.s. (Aliphatic Petroleum Distillate)

### 15. REGULATORY INFORMATION

All components of this product conform to the following national inventory requirements. US TSCA, EU EINECS and Canada DSL

#### SARA Title III

##### Section 302 – Extremely Hazardous Chemicals

The following ingredients are subject to the supplier notification requirements of Section 302 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 37 *None Listed*

##### Section 313 – Toxic Chemicals

The following ingredients are subject to the supplier notification requirements of Section 313 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part *None Listed*





# Safety Data Sheet

## REMA Tire Repair Materials

Product #: RTT- 40

SDS #: RTT-TRM-228

Rev. # 1

Rev. Date: 2/17/2023

---

### OTHER FEDERAL REGULATIONS

Components of this product are subject to RCRA Hazardous Waste requirements, Clean Air Act (CAA) Hazardous Air Pollutants requirements and OSHA Process Safety Management (PSM) high hazard requirements.

**CANADIAN REGULATIONS:** WHMIS Classification: Same as OSHA GHS Classification

### STATE REGULATIONS

#### California Proposition 65

This product does not contain materials known to the state of California to cause cancer, birth defects or other reproductive harm.

The components of this product may be included on the various state hazardous materials lists noted below.

California Hazardous Substances List/Permissible Exposure List

California Toxic air contaminants

Connecticut Permissible Exposure Limits

Delaware List of Chemicals and RQs

Hawaii Permissible Exposure Limits

Idaho Toxic Air Pollutants

Illinois Toxic Air Contaminants List

Louisiana Toxic Air Pollutants

Maine Hazardous Air Pollutants

Maryland Toxic Air Pollutants for Existing Sources

Massachusetts Hazardous Substances List

Michigan Permissible Exposure Limits

Minnesota Hazardous Substances

Minnesota Permissible Exposure Limits

Nebraska Hazardous Air Pollutants

New Jersey RTK Hazardous Substances List/TCPA Extremely Hazardous Substances List

New York List of Hazardous Substances

Ohio Toxic Air Contaminants

Oklahoma Toxic Air Contaminants

North Carolina TAP Emissions Rates Requiring a Permit

Pennsylvania Hazardous Substances List

Rhode Island Toxic Air Contaminants

Tennessee Permissible Exposure Limits

Vermont Hazardous Air Contaminants/Permissible Exposure Limits

Washington Permissible Exposure Limits for Airborne Contaminants.

West Virginia Toxic Air Pollutant List

Wisconsin hazardous Air Contaminants

**Note:** Entries under Section 15 are not intended to be all inclusive of Federal and State laws and regulations. Please consult the appropriate agencies for further clarification of any requirements.



# Safety Data Sheet

## REMA Tire Repair Materials

Product #: RTT- 40

SDS #: RTT-TRM-228

Rev. # 1

Rev. Date: 2/17/2023

### 16. OTHER INFORMATION

This SDS conforms to the OSHA Hazard Communication Standard 1910.1200 published in the Federal Register March 26, 2012

**MEDICAL EMERGENCIES:**

Call CHEMTREC 24 hours a  
Day for emergency information  
800-424-9300

**FOR ANY OTHER INFORMATION:**

REMA TIP TOP/NORTH AMERICA, INC  
300 Tice Blvd, Suite 250  
WOODCLIFF LAKE, NJ 07677  
201-256-8200

**NOTICE:** REMA TIP TOP NORTH AMERICA believes that the information contained on this safety data sheet is accurate. The suggested procedures are based on experience as of the date of publication. They are not necessarily all-inclusive, nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of, applicable laws, regulations, rules or insurance requirements.

**NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE.**